

DTM inkjet Label Stock

# DTM Paper High Gloss (non-permanent)

## Description

DTM Paper High Gloss (non-permanent) label materials have been designed specifically for use where excellent inkjet print quality and fast ink drying time is needed. It is ideal for applications printing variable information in conjunction with full-colour graphics. The non-permanent adhesive does not leave any kind of residue on application surface after removal. This label stock is designed for general purpose labelling.

## Face Stock

Special coating with a glossy finish. Suitable for high-resolution and high-speed dye based and pigmented inkjet printing.

## Adhesive

Acrylic, non-permanent adhesive. Water-borne and clear. Long-term removable without leaving residue on application surfaces.

## Liner

Super-calendered kraft with high internal tear resistance.

## Packaging and Shelf Life

Continuous or die-cut label rolls with identification labels. Each label roll is individually packed with a plastic bag. Keep label rolls in their plastic bags, in room temperature, away from direct sunlight and/or heat sources. Under ideal storage conditions, shelf life is two years.

## Product Usage

All DTM Genuine certified inkjet-materials are the ideal choice for labels printed on any colour label printer. Proper testing in the final application environment is recommended especially when used near water or chemicals. As with all pressure-sensitive materials, this product should be tested thoroughly with the chosen label printer under end-user conditions to ensure it will meet the requirements of the specific application.

## Technical Specifications

### Face

|         |        |                  |         |
|---------|--------|------------------|---------|
| Weight: | 85 ± 3 | g/m <sup>2</sup> | ISO 536 |
|---------|--------|------------------|---------|

|            |         |    |         |
|------------|---------|----|---------|
| Thickness: | 102 ± 4 | µm | ISO 534 |
|------------|---------|----|---------|

### Adhesive

|            |   |   |      |
|------------|---|---|------|
| Loop Tack: | 3 | N | FTM9 |
|------------|---|---|------|

|                |   |   |      |
|----------------|---|---|------|
| Peel Adhesion: | 1 | N | FTM2 |
|----------------|---|---|------|

### Liner/Backing

|         |        |    |         |
|---------|--------|----|---------|
| Weight: | 60 ± 2 | µm | ISO 534 |
|---------|--------|----|---------|

|            |        |    |         |
|------------|--------|----|---------|
| Thickness: | 57 ± 3 | µm | ISO 534 |
|------------|--------|----|---------|

### Performance

#### Minimum Application

|              |     |
|--------------|-----|
| Temperature: | 5°C |
|--------------|-----|

|                      |               |
|----------------------|---------------|
| Service Temperature: | -20°C to 80°C |
|----------------------|---------------|

DTM Print GmbH  
 Mainzer Strasse 131  
 65187 Wiesbaden  
 Germany  
 Phone: +49 611 92777-0  
 Email: sales@dtm-print.eu  
<http://dtm-print.eu>

