

DTM inkjet Label Stock

DTM Paper Matte (M)

Description

DTM Paper Matte label materials have been designed specifically to be highly absorbent to allow water based inkjet inks to set-up quickly. This characteristic while providing for immediate smudge resistance after printing, also makes the sheet highly receptive to airborne contaminants, which could result in a discolouration of the unprinted areas.

Face Stock

Special coating with a matte finish. Suitable for high-resolution and high-speed dye based and pigmented inkjet printing.

Adhesive

Acrylic, aggressive, permanent, general purpose adhesive. Water-borne and clear. Suitable for applications including apolar and rough surfaces.

Liner

White glassine.

Packaging and Shelf life

Continuous or die-cut label rolls with identification labels. Each label roll is individually packed with a plastic bag. Keep label rolls in their plastic bags, in room temperature, away from direct sunlight and/or heat sources. Under ideal storage conditions, shelf life is two years.

Product Usage

All DTM Genuine certified inkjet-materials are the ideal choice for labels printed on any colour label printer. Proper testing in the final application environment is recommended especially when used near water or chemicals. As with all pressure-sensitive materials, this product should be tested thoroughly with the chosen label printer under end-user conditions to ensure it will meet the requirements of the specific application.

Technical Specifications

Face

Weight:	88 ± 3	g/m ²	ISO 536
---------	--------	------------------	---------

Thickness:	113 ± 4	µm	ISO 534
------------	---------	----	---------

Adhesive

Loop Tack:	14	N	FTM9
------------	----	---	------

Peel Adhesion:	10	N/m	FTM2
----------------	----	-----	------

Liner/Backing

Basis Weight:	62 ± 2	g/m ²	ISO 536
---------------	--------	------------------	---------

Thickness:	55 ± 3	µm	ISO 534
------------	--------	----	---------

Performance

Minimum Application Temperature:	0°C
----------------------------------	-----

Service Temperature:	-20°C to 80°C
----------------------	---------------

DTM Print GmbH
 Mainzer Strasse 131
 65187 Wiesbaden
 Germany
 Phone: +49 611 92777-0
 Email: sales@dtm-print.eu
<http://dtm-print.eu>

